



CULTURE OF SOUND



ROX SERIES CATALOGUE

LATEST EDITION



ROX Series

PORTABLE CABINETS

The ROX Series is our answer to multi-purpose, full-range cabinets at affordable pricing.

The series comprises four self-powered, full range-cabinets with integrated FIR Filter DSP, BT connectivity and two channel mixer delivering exceptional sound quality value in a variety of environments.

Built with durability and portability in mind, the ROX Series is easy to transport, set up, and optimize for live performances, DJ sets, or corporate events. Its lightweight design, combined with a rugged build, makes it the go-to choice for professional sound technicians and event planners seeking reliable, high-quality sound.

- ✓ Installations in nightclubs & bars
- ✓ Large and medium-sized stadiums
- ✓ Live events

RX-8



The RX- 8 is a high-performance polypropylene, 2-way active PA system featuring a 8-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 8", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
Power	280W RMS / 600W Peak
Frequency Response	65 Hz to 20 kHz
SPL Max	118 dB - 124 dB Peak
Coverage	90°H x 60°V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Fittings	35mm (2-position) speaker stand socket and 45° angled wedge for stage monitoring
Power Supply	230V ~ / 50Hz mains power supply
Weight	12 Kg
Dimensions	435 x 245 x 295 mm (H x W x D)

RX-10



The RX- 10 is a high-performance polypropylene, 2-way active PA system featuring a 10-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 10", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
Power	280 W RMS / 600 W Peak
Frequency Response	45 Hz to 20 kHz
SPL Max	119 dB - 125 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for ea input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Fittings	35mm (2-position) speaker stand socket and a 45° angled wedge for stage monitoring
Power Supply	230V ~ / 50Hz mains power supply
Weight	15 Kg
Dimensions	545 x 355 x 295 mm (H x W x D)

RX-12



The ROX-12 is a high-performance polypropylene, 2-way active PA system featuring a 12-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 12", 3" voice coil HF: 1.35", compression driver
Amplification	Class-D
Power	450W RMS / 1000 W Peak
Frequency Response	45Hz to 20 kHz
SPL Max	125 dB - 131 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Fittings	35mm (2-position) speaker stand socket and 45° angled wedge for stage monitoring
Power Supply	230V ~ / 50Hz mains power supply
Weight	21 Kg
Dimensions	609 x 359 x 346 mm (H x W x D)

RX-15



The ROX-15 is a high-performance polypropylene, 2-way active PA system featuring a 15-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W, making it ideal for sound reinforcement in both indoor and outdoor environments.

Components	LF: 15", 3" voice coil HF: 1.35", compression driver
Amplification	Class-D
Power	450 W RMS / 1000 W Peak
Frequency Response	45 Hz to 20 kHz
SPL Max	125 dB 131 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Fittings	35mm (2-position) speaker stand socket and 45° angled wedge for stage monitoring
Power Supply	230V ~ / 50Hz mains power supply
Weight	23 Kg
Dimensions	696 x 417 x 368 mm (H x W x D)



LYNX

pro-audio

CULTURE OF SOUND



www.lynxproaudio.com