



CULTURE OF SOUND



KR SERIES CATALOGUE

LATEST EDITION



KR Series

PASSIVE CABINETS FOR CLUBS & KTV


The two full-range models belonging to the KR Series have been specifically designed for installations where high volume is required whilst delivering excellent vocal clarity with low distortion. They are available in two-way passive 10" and 12" versions.

Ideal for a wide range of fixed installation applications, such as KTV rooms, conference halls, houses of worship or multimedia spaces.

The double port located at the rear of the enclosure creates increased bass frequency response. When installed close to a wall, it creates a reflection that extends the low frequency response of the system, creating extra bass boost.

- ✓ KTV rooms
- ✓ Public buildings
- ✓ Houses of worship
- ✓ Conference halls
- ✓ Clubs & bars
- ✓ Sound reinforcement
- ✓ Multi media spaces

KR-12



The KR-12 is a compact, two-way passive cabinet. Consists of a 12" (3" voice coil) LF transducer with total waterproof cone treatment. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

Components	LF: 12" speaker, 3" (75 mm) copper wire voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphragm driver
Max SPL	124 dB / 130 dB Peak
Dispersion	90° x 60° rotatable
Rated power	500 W AES (1000 W program, 2000 W Peak)
Dimensions	600 x 363 x 410 mm (H x W x D)
Weight	24 Kg (52.9 lbs)
Fittings	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 4 x M6 wall bracket, 35 mm top hat

KR-10



The KR-10 is a compact, two-way passive cabinet. Consists of a 10" (2.5" voice coil) LF transducer with waterproof cone. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

Components	LF: 10" speaker, 2.5" (50 mm) fiber glass former and aluminium winding voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphragm driver
Max SPL	122 dB / 128 dB Peak
Dispersion	90° x 60° rotatable
Rated power	300 W AES (600 W program, 1200 W Peak)
Dimensions	550 x 295 x 330 mm (H x W x D)
Weight	16 Kg (35.2 lbs)
Fittings	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 6 x M6 wall bracket, 35 mm top hat

ACCESSORIES **KR** SERIES

KR-10	AGR-8 Eye bolt	WB-20/3 Wall bracket	UBR-KR10 U bracket
			
KR-12	AGR-8 Eye bolt	WB-20/3 Wall bracket	UBR-KR12 U bracket
			



LYNX

pro-audio

CULTURE OF SOUND



www.lynxproaudio.com